

RhinoLite® Grippon® Bonding Liquid



Benefits



Ensures strong adhesion of **RhinoLite®** to previously painted surfaces



Compatible with multiple surfaces



Ready-to-Use Bonding Liquid



RhinoLite® Grippon® Bonding Liquid is a pink, acrylic-based primer specially formulated to enhance the adhesion of gypsum and sand/cement plasters to previously painted, plastered, or concrete surfaces.

RhinoLite® Grippon® Bonding Liquid



RhinoLite® Grippon® Bonding Liquid is a ready-to-use bonding agent designed to improve the adhesion of gypsum plasters.

It is formulated for consistent performance and is ideal for use on previously painted, plastered or concrete surfaces.

USE

RhinoLite® Grippon® Bonding Liquid is used as part of the surface preparation when applying:

- RhinoLite® gypsum plaster to previously painted surfaces
- RhinoLite® gypsum plaster to concrete surfaces

SUITABLE SURFACES

RhinoLite® Grippon® Bonding Liquid is suitable for use on surfaces like:

- Cement-based plaster
- Concrete
- RhinoBoard® plasterboard
- Fibre-cement

SURFACE PREPARATION

Ensure that all surfaces are clean, dry, sound and free from dust, grease or any contamination that could impair bonding. Oil or grease should be removed using a cleaning agent and rinsed thoroughly with clean water.

APPLICATION

General

The final coat of RhinoLite® Grippon® Bonding liquid must be wet or tacky when the plaster is applied. If you are unsure about the surface's absorption level, perform a small bond test to determine the correct treatment.

• Average absorption surfaces:

Apply one liberal coat using a brush or roller.

• High absorption surfaces:

Apply two liberal coats. Allow the first coat to dry completely before applying the second.

• Very high absorption surfaces:

Pre-wet the surface with clean water, then apply two liberal coats. Let the first coat dry before applying the second.

Clean brushes and rollers with clean water after use.

MIXING

RhinoLite® Grippon® Bonding Liquid is supplied ready for use. Do not add water. Stir thoroughly to maintain uniform suspension of solids.

South Africa, 07/2025. Gyproc reserves the right to modify data without prior notice. If required, please contact the Gyproc Technical Department. Saint-Gobain Construction Products South Africa (Pty) Ltd. Reg no: 1937/010220/07

COVERAGE

Approximately 9 m² per litre, per coat, depending on surface texture and application method.

PACKAGING

RhinoLite® Grippon® Bonding Liquid is supplied in 5 and 20 litre plastic containers.

STORAGE & SHELF LIFE

Store unopened in a dry place below 50°C. Shelf life is 12 months from the date of manufacture. Reseal tightly after use. Store above 5°C to prevent freezing.

FEATURES & BENEFITS

- Consistent, high-quality formulation
- Strong bonding performance
- Reliable plaster bonding agent
- Suitable for interior application

SAFETY INSTRUCTIONS

Ensure adequate ventilation during use. Avoid inhaling vapours and prevent contact with skin and eyes. Wear appropriate personal protective equipment such as safety glasses, gloves, and protective clothing when necessary.

Keep out of reach of children and pets. Store away from incompatible chemicals and avoid contact with sensitive surfaces. Do not ingest. Product is flammable above 190°C, do not use near open flames or intense heat sources.

PACKAGING MATERIAL

Material Code	Sales Packaging
23026	5L Bucket
23027	20L Bucket



SAINT-GOBAIN

GYPROC a division of Saint-Gobain
Construction Products SA (Pty) Ltd
300 Janadel Avenue • Halfway House

• Midrand 1686 • South Africa
PO Box 50416 • Randjiesfontein

• 1683 • South Africa
+27 (0)12 657 2800

www.gyproc.co.za