

RhinoLite® RhinoFill™

Ready Mixed Dual Purpose Crack Filler

Product Data Sheet

Advantages



Environmentally
friendly



Durability



Neat finish



RhinoLite® RhinoFill™ Ready Mixed Crack Filler, is suitable for interior and exterior applications, available in a paste form, has low shrinkage, excellent adhesion and can be applied in layers of up to 5 mm. It can be sanded to a smooth finish.



RhinoLite®

RhinoFill™

Ready Mixed Crack Filler

About this product

RhinoLite® RhinoFill™ Ready Mixed Crack Filler, is suitable for interior and exterior applications.

Storage and shelf-life and disposal

Store away from direct sun, heat and severe cold. Protect from freezing.

Packaging

RhinoLite® RhinoFill™ Ready Mixed Crack Filler is supplied in 2 kg and 5 kg tubs.

Features and benefits

- ▶ Suitable for sand/cement, plaster, plaster boards, concrete, stone and other masonry surfaces.
- ▶ Can be used straight from the tub.
- ▶ It is slump resistant and can be applied in thick layers up to 5 mm.
- ▶ Excellent strength, good adhesion and abrasion resistance.

Safety instructions

- ▶ Ensure good ventilation during application and drying.
- ▶ Wash skin contamination away with warm soapy water.
- ▶ Avoid contact with eyes. In case of accidental contact immediately rinse with plenty of clean water and contact a doctor.
- ▶ Do not ingest.

Surface preparation

- ▶ Clean away dust, grease and grime from surface
- ▶ Ensure that surfaces are thoroughly clean and completely dry.

Mixing

- ▶ Ready mixed.
- ▶ Stir if there are signs of liquid separation on top, ensure that it is thoroughly mixed before application.
- ▶ Make sure that all tools are clean and free of any contamination such as previously set material as this may reduce the strength of the product.

RhinoLite® RhinoFill™

Ready Mixed Crack Filler

Application

- ▶ Use a clean scraper/putty knife.
- ▶ Make sure that product is properly mixed.
- ▶ Fill the cracks, holes and indentations using a scraper or putty knife.
- ▶ Apply in layers from 1mm to 5 mm thick. For deeper cracks, holes or indentations should be done in two or more steps.
- ▶ Even out the RhinoLite® RhinoFill™ Ready Mixed Crack Filler while wet to level with the surrounding surface. Best applied when mix is wet.
- ▶ Allow to fully dry before sanding, drilling or painting. Drying times are dependent on thickness of application and atmospheric conditions. Apply a universal undercoat before painting.
- ▶ Should sanding still be required – use wet 100 grit waterproof sandpaper to obtain the best results.

Guarantee

RhinoLite® RhinoFill™ Ready Mixed Crack Filler meets the product specifications and will be free from any defect. Any guarantee with regard to the performance of the products will be subject to the professional and practical application in accordance with our instruction and specification on this packaging.

However, we have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain professional advice. Should our product prove defective, we undertake to replace any defective material. This guarantee will fall away in the event of product being contaminated by the addition of sand, cement or substances other than recommended by us.

Technical services

The product should be used as directed – consult specification data for further details. The RhinoFill™ Ready Mix Crack Filler data sheet should be made available to all personnel using/handling the product. Contaminated clothing should be removed and washed before re-use.

Notice to User: This product data sheet should not constitute the users' own workplace risk assessment.

Obtain information about products via Internet:
www.gyproc.co.za/products/plasters



GYPROC a division of Saint-Gobain
Construction Products SA (Pty) Ltd

Block A, Siemens Office Park
300 Janadel Avenue • Halfway Gardens
Midrand 1686

PO Box 50416 • Randjesfontein
1683 • South Africa

+27 (0)12 657 2800

www.gyproc.co.za



Saint-Gobain Construction Products South Africa (Pty) Ltd (SGCPSA) is a limited liability company registered in South Africa under company registration number 1937/010220/07. SGCPSA reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the Gyproc SA website at: gyproc.co.za.